

The VESDA-E VEA series of aspirated detectors combine VESDA reliability and early warning smoke detection with pinpoint addressability and a variety of annunciation options. They use patented air sampling points and multi-channel microbore air-sampling with three alarm sensitivity settings for the sampling points. As a multi-channel addressable system, the VEA detector is able to divide a protected space into sampling locations, enabling the localization of potential sources of fire for faster incident response.



The detectors are suitable for protection of areas where pinpoint location of fire events is essential, thus providing ideal fire detection solutions for healthcare, offices, education, retail, prisons and electrical cabinets. A wide range of features provide flexibility, field programmability, enhanced connectivity and reduced total cost of ownership.

### Installation, Commissioning and Maintenance

The VEA detector features a robust IP40-rated enclosure and is equipped with a powerful pump that provides up to 100 m (328 ft) microbore tube length. It is fully supported by the Xtralis VSC software which facilitates ease of system commissioning and maintenance. During commissioning, the normalization process establishes the flow performance parameters. Local smoke test ports are used during servicing to verify that the system is fully operational. Field replaceable filter, smoke sensor module, pump and rotary valve components result in less down time and ease of maintenance.

### Color LCD Display

The VEA-040-A10 detector features a 3.5" colour LCD display which provides a range of status information including alarm and fault conditions as well as smoke level. Screens for each type of information are available using a simple navigation system.

### VESDAnet™

VESDA detectors and devices communicate on VESDAnet which provides a robust bi-directional communication network allowing continued redundant operation even during single point wiring failures. VESDAnet enables primary reporting, centralized configuration, control, maintenance and monitoring.

### Ethernet Connectivity

VESDA-E detectors offer connectivity to corporate networks via Ethernet, allowing for devices installed with Xtralis monitoring and configuration software to connect to the detector.

## Features

- Pinpoint addressability
- 40 addressable microbore tubes with individual sampling points
- Assured detection with end to end system integrity monitoring
- Interruption-free business operation with centralised testing and maintenance
- Single sampling point or single tube blockage detection at set intervals
- Automatic sampling point presence and tube breakage detection at set intervals
- Automatic sampling point cleaning at set intervals
- Three sensitivity settings for the sampling points
- Variable length capillary tubes, up to 100 m (328 ft)
- Laser-based absolute smoke detection
- Coarse particle filtering and clean air barrier for optics protection
- Reliable linear pump technology
- LEDs for alarm and fault signalling
- 3.5" colour touch screen for status review
- Seven programmable relays
- Two GPIs, monitored and unmonitored
- Xtralis VSC and VSM4 PC software support
- IP 40 enclosure (not UL tested)
- Easy mounting with steel support bracket
- Field replaceable filter, smoke sensor module, pump and rotary valve
- VESDAnet networking
- Ethernet 100BASE-T
- Local host-mode USB port
- Easy cable termination access
- Event Log (20,000 events)

### Listings / Approvals

- EN 54-20, ISO 7240-20: Class A, B and C
- CE
- UKCA
- VdS
- ActivFire (ISO 7240-20)
- FM

Regional approvals listings and regulatory compliance vary between product models. Refer to [www.xtralis.com](http://www.xtralis.com) for the latest product approvals matrix.

**Important Note:** 30<sup>th</sup> of June 2024 was the last date VESDA-E VEA-040-A00 and VEA-040-A10 smoke detectors were manufactured for the UL market. Any reference to UL in this document is applicable only to VEA smoke detectors manufactured on or before the 30<sup>th</sup> of June 2024.

## How it works

The VEA detector draws a combined air sample from a network of microbore flexible tubing from all sampling points in the protected area, then filters and analyzes the sample in laser detection chambers in the smoke sensor module. When smoke particles are detected and the smoke level reaches set alarm thresholds, the system will raise appropriate alarm conditions. After a Fire 1 alarm is raised, the system will sequentially scan the sampling locations via the rotary valve to identify one or more sampling locations with the fire alarm event. To assist in investigation of the source of a fire, if the system is in Pre-Alarm, the user can initiate a smoke scan of all sampling locations.

The VEA uses a vacuum pump which provides superior detection times for long tube lengths. The system monitors the airflow within the installation, allowing detection of breakages or blockages of individual sampling points and sampling tubes at set intervals, with faults indicated on the display and to the monitoring equipment.

Alarms and fire location can be signaled via Relays and VESDAnet. Ethernet can be used for configuration and secondary monitoring, and a USB interface is provided for field installation and maintenance. The optional Relay StaX module can be used to identify and signal fire source locations on a fire panel loop.

A series of LEDs display Alarm, Trouble, Disable and detector power on status. A button allows the user to Reset or Disable the detector. Additionally, the VEA-A10 features a 3.5" LCD display which shows detector status.

## Specifications

<b>Supply Voltage</b>	18-30 VDC	
<b>Power Consumption @ 24VDC</b>	<b>VEA-040-A00</b>	<b>VEA-040-A10</b>
<b>Quiescent</b>	27 W	27 W
<b>Alarm Average</b>	27 W	27 W
<b>Peak current (scan mode)</b>	3.5A	
<b>Aspirator</b>	Linear Vacuum Pump	
<b>Dimensions (WHD)</b>	352 mm x 336 mm x 135.5 mm (13.9 in x 13.2 in x 5.33 in)	
<b>Weight</b>	9.9 kg (21.8 lbs)	10 kg (22.2 lbs)
<b>Operating Conditions</b>	Ambient: 0°C to 38°C (32°F to 100°F) Sampled Air: 0°C to 50°C (32°F to 122°F)* Humidity: 5% to 95% RH, non-condensing  <i>* Sampled Air temperature shall reach Ambient Detector temperature upon entry into Detector. Refer to Xtralis Design Guides &amp; Application Notes for sampled air pre-conditioning.</i>	
<b>Microbore Tube Size</b>	Normal Diameter: OD 6 mm, ID 4 mm Reduced Diameter: OD 4 mm, ID 2.5 mm	
<b>Microbore Tube Length</b>	Normal Diameter: Up to 100m (328 ft) per tube Reduced Diameter: Up to 15 m (49 ft) per tube	
<b>Flow Monitoring</b>	Single sampling point and single tube blockage and breakage detection at set intervals	
<b>Relays</b>	7 programmable relays (latch or non-latch states) Contacts rated 2 A @ 30 VDC (Resistive)	
<b>IP Rating</b>	IP40	
<b>Cable Access</b>	4 x 25 mm (1") cable entries	
<b>Cable Termination</b>	Screw Terminal blocks 0.2–2.5 sq mm (24 - 14 AWG)	
<b>Pre-alarms</b>	Alert and Action - two pre alarm levels	
<b>Fire-1 Alarm Thresholds at the Sampling Hole</b>	High: 1.6 % obs/m (0.5 % obs/ft) Enhanced: 4.0 % obs/m (1.23 % obs/ft) Standard: 8.0 % obs/m (2.5 % obs/ft)	
<b>Communication Interfaces</b>	USB 2.0, Ethernet (RJ45)	
<b>Software Features</b>	Event log: Up to 20,000 events. Smoke level, user actions, alarms and faults with time and date stamp	

## Ordering Information

Ordering Code	Description
<b>VEA-040-A00</b>	VESDA-E VEA-40 Aspirating Smoke Detector with LEDs
<b>VEA-040-A10</b>	VESDA-E VEA-40 Aspirating Smoke Detector with 3.5" Display
<b>VER-A40-40-STX</b>	VESDA-E VEA 40-Relay Local StaX

Refer to VEA Sampling Points data sheet (document # 29730) for more information regarding the sampling points.

## Spare Parts

Ordering Code	Description
<b>VSP-970</b>	VESDA-E VEA-40 Mounting Bracket
<b>VSP-971</b>	VESDA-E VEA-40 Smoke Sensor Module
<b>VSP-972</b>	VESDA-E VEA Filter
<b>VSP-973</b>	VESDA-E VEA Pump
<b>VSP-974</b>	VESDA-E VEA Rotary Valve
<b>VSP-975</b>	VESDA-E VEA-040-A00 Fascia with LEDs
<b>VSP-976</b>	VESDA-E VEA-040-A10 Fascia with 3.5" Display
<b>VSP-1006</b>	VESDA-E VEA Volumetric Chamber

## Approvals Compliance

Please refer to the Product Guide for details regarding compliant design, installation and commissioning.